



The Das Console range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring , troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.


Available with 17" or 19" A-Grade LCD panels, combo DB15 single , 8 or 16 port integrated KVM switch & additional one USB local console.

## Features

- Support combo interface,VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVM-1701/1901AST-M6/ULC



Rear of KVM-1708/1908AST-M6/ULC



Rear of KVM-1716/1916AST-M6/ULC


Part No.	KVM-1701AST-M6/ULC	KVM-1708AST-M6/ULC	KVM-1716AST-M6/ULC	KVM-1901AST-M6/ULC	KVM-1908AST-M6/ULC	KVM-1916AST-M6/ULC
Direct no. of Computers	1	8	16	1	8	16
Maximum no. of Computers	1	232(Daisy Chain)	240(Daisy chain)	1	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"		19"		
	Backlight	LED		LED		
	Resolution	1280*1024		1280*1024		
	Max.color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	176 / 170		170 / 160		
Contrast Ratio	1000 : 1		1000 : 1			
Port Selection	N/A	Push Button,OSD or Hotkey		N/A	Push Button,OSD or Hotkey	
USB Local console	Yes , USB x2 for KB/ Mouse , VGA x1					
KB/Mouse Emulation	USB & PS2					
Rack Depth	500mm to 1100mm ( rack cabinet front rails to rear rails )					
Power	100-240V AC 50/60Hz via IEC Type power cord					
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP					
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG			448x42x580mm (WxHxD) / 12.5KG		
Packing Dimensions / Gross weights	720x190x800mm (WxHxD) / 18.0KG			720x190x800mm (WxHxD) / 18.5KG		
<b>Accessory</b>						
1.8meter IEC Type Power Cord						
<b>Option Relate Item</b>						
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA		CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA		CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA		CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA		



Rear of KVM-1701/1901AST-M6/ULC



Rear of KVM-1708/1908AST-M6/ULC



Rear of KVM-1716/1916AST-M6/ULC

