



High performance ZeroU™ IP KVM dongle for extension or matrix of video, audio and USB over a single cable.

ADDERLink® INFINITY 101T (ALIF101T) is a high performance ZeroU IP KVM extender with matrix capability that enables the use of standard IT infrastructure to extend computers away from the user environment.

ADDERLink® INFINITY 101T DVI

Matrix

Features



ZeroU™ Form Factor

The ADDERLink INFINITY 101T (ALIF101T) takes ZeroU of rack space in the server room allowing for ultimate flexibility and ease of installation.



Perfect Digital Video, Real-Time Control

Using a spatially-lossless encoding system, with 1:1 pixel mapping, the ALIF101T provides pixel-perfect and color accurate video with no artifacts. The digital video received is the same as the digital video leaving the remote computer.



USB Powered

The device can be powered from USB. This means there is no need to provision for an external PSU. Options for powering from an external PSU or redundant PSU are also available.



USB 2.0 with Class Control

Supports USB devices including graphics tablets, jog shuttles, joysticks and 3D explorers, alongside mass storage devices. For secure applications, the system can disable the use of non-HID devices, meaning there is no need to physically block USB ports to prevent the use of mass storage devices.




Support for Dithered Video

Allows analog or noisy video to pass through the system, along with computers, that dither the video to enhance the perceptive image quality. Some Mac computers use this technique.



ADDERLink INFINITY Matrix

With the addition of the ADDERLink INFINITY Management (AIM) system, you can turn multiple point-to-point extenders into a scalable digital KVM matrix system that allows any workstation to link with any computer connected to the network.



EDID Management

Intelligent EDID management allows the true characteristics of the monitor to be passed back to the computer. This ensures perfect video display without additional configuration.



Plug and Play

ADDERLink INFINITY devices are delivered in a zero config state so you can plug them in and start working on them straight away. There is no need for drivers or software to be installed.



Digital Audio

The system can deliver USB stereo audio (bi-directional) or embedded video standard stereo audio (uni-directional).



Low Power Consumption

At under three watts of power in typical usage, the ALIF101T radically reduces the requirements for power supply capacity and air-conditioning in most installations

Video Information (1 Screen)		
Maximum Resolution (1 Screen)		1920 x1200
Frame Rate (1 Screen)		60
Color Depth (1 Screen)		8 bpc
Computer Connections		
USB A		2x 2.0, True Emulation,Full Speed,Low Speed,High Speed
DVI-D		1x
Link Ports		
8p8c (RJ45)		1x
Audio Connections		
Audio Type		Digital
Channels		2x
Audio Direction		Bi-directional
Size (bit)		16
Speed (kHz)		48
Audio In Port		1x USB
Cable Requirements		
CAT5e and above		100m / 328ft
CAT5e		100m / 328ft
CAT6 (SFTP)		100m / 328ft
CAT6a		100m / 328ft
CAT7		100m / 328ft
Network Support		
Bandwidth		1GbE
10/100 Support		No
Environmental		
Operating Temperature Range °C / °F		0 to 50 °C / 32 to 122 °F
Storage Temperature °C / °F Range		-10 to 60 °C / 14 to 140 °F
Operating Humidity (%)		10% - 90% (non-condensing)
Storage Humidity (%)		10% - 90% (non-condensing)
Altitude m/ft		2,000 / 6562
Mean Time Between Failure (MTBF)		1,200,000 h
MTBF Standard		Telcordia SR332 Issue 4 March 2016 Calculated @

Power Source	
USB powered	2x
5V	1x
Power Additional Information	USB power: 2x USB2.0 (2x 500mA @5V) 5W• External power: 5VDC, 1A, (LPS)
Power Consumption	
Maximum Power (Watts)	5
Typical Power (Watts)	3
Physical Design	
Construction Material	ABS and aluminium construction
U size	0
Width (mm) / (in.)	55 / 2.2
Height (mm) / (in.)	25 / 1
Depth (mm) / (in.)	110 / 4.3
Flying Lead Length (mm)	300
Weight (kg) / (lb)	0.2 / 0.4
Compatibility	
OS Compatibility	All known operating systems
Approvals and Standards	
Approvals	CE, cULus - E476334, FCC, ICES, UKCA
Standards	ANSI 63.4, EN/IEC 62368-1, EN55032 /CISPR 32, EN55035/CISPR 35, EN63000, FCC pt15B, ICES003
Other	Cal Prop 65, China ROHS, EU REACH, UK REACH
Packing Box	
Length (mm) / (in.)	292 / 11.5
Width (mm) / (in.)	245 / 9.6
Depth (mm) / (in.)	55 / 2.2
Weight (kg) / (lb)	0.5 / 1.1



What's in the Box?

1x ALIF101T unit

1x Quick start guide

Ordering Information

ALIF101T-DVI ALIF101T- DVI Transmitter

Related Accessories (Sold Separately)

ADDER® Power Supply Unit 5volt DC 2.5A

ADDER® DVA

ADDER® PSU RED PRO 12V to 5V DC converter

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.